

Product Information Bulletin

P.O. Box 467 | 64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809



Tamper Resistant Fence Bracket

SignGuardian™



The SignGuardian™ Lock-On Feature™ holds the bracket securely to the fence mesh, and is tamperproof once the sign or banner is installed.



Lock-On Feature™ ready for installation



Lock-On Feature™ deployed. SignGuardian™ is now secured from twisting or prying from behind the sign.



Lock-On Feature™ is inaccessible behind installed sign!

- Signs now can be installed from either side of the fence
- SignGuardian™ brackets are made of Nylon 6/6, which is extremely strong!
- SignGuardian™ provides security to signs mounted on chain link fencing!
- Easy Installation!
- Vertical and Horizontal travel to connect holes.
- Lock on Fence feature.
- Nut locked inside slot.

SIZE & CONFIGURATION AVAILABLE

Product Made in the USA

Part Number:	Item Description	Application/Mounting
Y4961 (2 Brackets)	Fence Bracket with 1-Way R™ Bolt for Traffic/Parking Signs (Includes 2 brackets, 2 nuts, 2 One way bolts 5/16" x 1")	To mount 1 sign only with 2 holes at 3/8"
Y4960 (10 Brackets)	Fence Bracket with 1-Way R™ Bolt Package of 10 Brackets w/ nuts and one way bolts 5/16" x 1")	To mount signs with 2 holes at 3/8"
Y4963 (4 brackets)	Fence Bracket with 1-Way R™ Bolt for Safety Signs (Includes 4 brackets, 4 nuts, 4 One way bolts 10/24" x 1")	To mount 1 sign only with 4 holes at 3/16"
Y4962 (20 brackets)	Fence Bracket with 1-Way R™ Bolt for Safety Signs (Includes 4 brackets, 4 nuts, 4 One way bolts 10/24" x 1")	To mount signs with 4 holes at 3/16"

DATE: ___ / ___ / ___

JOB: _____

CONTRACTOR: _____

Product Information Bulletin

P.O. Box 467 | 64 Outwater Lane, Garfield, NJ 07026 Ph: 973-340-7889 | Fax: 973-340-7809







Tamper Resistant Fence Bracket

Bracket Installation:

The most common size of chain link fencing is a 2" diamond with a front and rear side. Install this bracket on the rear side and it will become flush with the front side to mount the sign.

- A - Slide the front right side of the SignGuardian onto the top-right REAR side of the diamond.
- B - Swivel the bracket inward onto the bottom left side of the diamond.
- C - Slide the SignGuardian left onto the fence.
- D - Tighten the set screw.



SIGN INSTALLATION

A - Install your sign with using the 1 inch 1 Way R Bolt™
Put bolt through TOP hole and engage nut, leave loose.

B - Straighten sign until 2nd hole is aligned and engaged.
Next put bolt through your signs BOTTOM hole.



DATE: ___ / ___ / ___

JOB: _____

CONTRACTOR: _____